

**SUMMARY TEST DATA  
ON  
P4T-500M40G-60-T-55-292FF-SP Rev. B**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P4T-500M40G-60-T-55-292FF-SP Rev. B  
 Serial No: PL41987/2335

Tested By: L. McGraw  
 Temperature: +25° C  
 Date: 8/31/2023  
 Drawing No: 27613629-B      Rev: B2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE			TEST RESULTS	QA QC
1	Frequency Range:	0.5 - 40 GHz			0.5 - 40 GHz	PMI QA2
2	Insertion Loss:	8.0 dB Max.			6.5 dB See Graph	
3	Isolation:	60 dB Min.			76 dB See Graph	
4	VSWR: In/Out	2.5:1 Max. 2.0:1 Typ.			2.41:1 In 2.43:1 Out See Graph	
5	Input Power:	+20 dBm CW Max.			Pass See Typical Characteristics	
6	Survival Power:	1 W Peak 1 $\mu$ s			Pass See Typical Characteristics	
7	RF Switching Speed:	Rise/Fall: 15 ns Max. Delay On/Off 50 ns Max.			<15 ns Rise/Fall <50 ns Delay See Typical Characteristics	
8	DC Supply:	+5 VDC @ 250 mA Max. -5 VDC @ 100 mA Max.			+5 VDC @ 124 mA -5 VDC @ 60 mA	
9	Control Signal:	E1	E2	Function	Pass	PMI QA2
		0	0	J1-J2 "Low Loss"		
		0	1	J1-J3 "Low Loss"		
		1	0	J1-J4 "Low Loss"		
		1	1	J1-J5 "Low Loss"		

QA/QC Approval: 

PMI  
QA2

Date: 8/31/2023

# SUMMARY TEST DATA ON P4T-500M40G-60-T-55-292FF-SP Rev. B

