



SUMMARY TEST DATA
ON
P8T-10G31G-70-T-55-292FF-ROHS

Customer: _____
 SO No: _____
 Model No: P8T-10G31G-70-T-55-292FF-ROHS
 Serial No: PL42164/2338

Tested By: L. McGraw
 Temperature: 25°C
 Date: 9/21/2023
 Drawing No: 27645620 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	10 GHz to 31 GHz	10 GHz to 31 GHz	PMI QA2	
2	Isolation	70 dB Min.	83.4 dB		
3	Insertion Loss	8 dB Max.	6.29 dB		
4	VSWR: In/Out	2.0:1 Max.	1.97:1 In 1.99:1 Out		
5	Operating Power CW	20 dBm	Pass See Typical Characteristics		
6	Switching Speed Typ	50 ns Typ.	Pass See Typical Characteristics		
7	Power Supply	5 V @ 250 mA -5 V @ 100 mA	5 V @ 196 mA -5 V @ 60 mA		
8	Control Signal	TTL LOGIC '1' : Insertion Loss '0' : Isolation	Pass		PMI QA2

QA/QC Approval: PMI QA2

Date: 9/21/2023

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@quanticpmi.com



