



**SUMMARY TEST DATA**  
**ON**  
**P4T-218-60-R-2W-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P4T-218-60-R-2W-SFF  
 Serial No: PL42757/2344

Tested By: S. O'Neill  
 Temperature: 25°C  
 Date: 11/8/2023  
 Drawing No: 27646680 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	2 GHz to 18 GHz	2 GHz to 18 GHz	PMI QA2	
2	Insertion Loss	3.2 dB Max.	2.91 dB		
3	Isolation	60 dB Min.	70.4 dB		
4	VSWR: In/Out	2:1 Max.	1.58:1 In 1.61:1 Out		
5	Switching Speed	100 ns Max.	Pass See Typical Characteristics		
6	Operating Power	1 Watts CW Max 2 Watts Peak Max	Pass See Typical Characteristics		
7	Power Supply	5 to 15 V @ 95 mA -15 to -5 V @ 65 mA	15 V @ 76 mA -15 V @ 15 mA		PMI QA2

QA/QC Approval:  PMI QA2

Date: 11/9/2023

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com



