

**SUMMARY TEST DATA  
ON  
JTIDS-0001-SFM**

CUSTOMER: \_\_\_\_\_ TESTED BY: H. Gonzales / A. Lopez  
 SO: \_\_\_\_\_ TEMPERATURE: +25°C  
 MODEL NO: JTIDS-0001-SFM DATE: 11/29/2023  
 SERIAL NO: PL42961/2348 DRAWING NO: 27646040 REV: A1

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	Center Frequency	1085 MHz	1085 MHz	PMI QA2
2	Notched Bandwidth	250 MHz	250 MHz	
3	Passband Insertion Loss	6.0 dB MAX	3.72 dB (DC to 910 MHz)	
		(DC - 910 MHz, 1260 - 2000 MHz)	3.71 dB (1260 to 2000 MHz)	
			See Graph	
4	Passband VSWR	2.0:1 TYP 3.5:1 MAX AT PASSBAND EDGES	2.09 :1 See Graph	
5	Rejection	-40 dBC MIN @ 960 to 1210 MHz	44.65 dBC See Graph	PMI QA2

QA/QC Approval:  PMI QA2 Date: 11/30/2023

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731  
 Email: sales@pmi-rf.com

### SUMMARY TEST DATA ON JTIDS-0001-SFM

