

SUMMARY TEST DATA ON JTIDS-0001-SFM

CUSTOMER:

SO:

TESTED BY: H. Gonzales / A. Lopez

TEMPERATURE: +25°C

MODEL NO: JTIDS-0001-SFM

DATE: 11/29/2023

SERIAL NO: PL42963/2348

DRAWING NO: 27646040

REV: A1

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	Center Frequency	1085 MHz	1085 MHz	PMI QA2
2	Notched Bandwidth	250 MHz	250 MHz	
3	Passband Insertion Loss	6.0 dB MAX (DC - 910 MHz, 1260 - 2000 MHz)	3.71 dB (DC to 910 MHz)	
			4 dB (1260 to 2000 MHz)	
			See Graph	
4	Passband VSWR	2.0:1 TYP 3.5:1 MAX AT PASSBAND EDGES	2.09 :1 See Graph	
5	Rejection	-40 dBC MIN @ 960 to 1210 MHz	45.25 dBC See Graph	PMI QA2

QA/QC Approval:

PMI
QA2

Date:

11/30/2023

SUMMARY TEST DATA ON JTIDS-0001-SFM

