

**SUMMARY TEST DATA
ON
JTIDS-0001-SFM**

CUSTOMER: _____ TESTED BY: H. Gonzales / A. Lopez
SO: _____ TEMPERATURE: +25°C
MODEL NO: JTIDS-0001-SFM DATE: 11/29/2023
SERIAL NO: PL42965/2348 DRAWING NO: 27646040 REV: A1

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	Center Frequency	1085 MHz	1085 MHz	PMI QA2
2	Notched Bandwidth	250 MHz	250 MHz	
3	Passband Insertion Loss	6.0 dB MAX (DC - 910 MHz, 1260 - 2000 MHz)	3.85 dB (DC to 910 MHz)	
			3.69 dB (1260 to 2000 MHz)	
			See Graph	
4	Passband VSWR	2.0:1 TYP 3.5:1 MAX AT PASSBAND EDGES	2.05 :1 See Graph	
5	Rejection	-40 dBC MIN @ 960 to 1210 MHz	44.65 dBC See Graph	PMI QA2

QA/QC Approval:  PMI
QA2

Date: 11/30/2023

SUMMARY TEST DATA ON JTIDS-0001-SFM

