



SUMMARY TEST DATA
ON
LM-10M14G-100W-1KWP-SFF-OPT17

Customer: _____
SO No: _____
Model No: LM-10M14G-100W-1KWP-SFF-OPT17
Serial No: PL43015/2348

Tested By: John R.
Temperature: +25°C
Date: 11/29/2023
Drawing No: 27637020 REV: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	10 MHz to 7 GHz	10 MHz to 7 GHz	PMI QA2
2	Insertion Loss:	2 dB Typ.	0.91 dB See Graph	
3	Input/Output VSWR:	2.0:1 Max. @ -10 dBm Input	1.84:1 In 1.8:1 Out See Graph	
4	Impedance:	50 Ω	Pass	
5	Max. CW Input Power:	100W CW Max. (1.0 GHz to 7.0 GHz) All Temperatures (-55°C to +85°C)	Pass See Typical Characteristics	
6	Max. Pulsed Peak Power Handling:	1KW Peak (1% Duty Cycle, 1 μ s Pulse Width) 100W Peak (10% Duty Cycle, 10 μ s Pulse Width)	Pass See Typical Characteristics	
7	Max. Flat Leakage:	+17 dBm Typ. @ 100W CW	Pass See Typical Characteristics	
8	P1dB:	+ 5 dBm Min.	+ 5 dBm See Graph	
9	Recovery Time:	100 ns Max.	Pass See Typical Characteristics	PMI QA2

QA/QC Approval: *Cameron Heley* PMI QA2

Date: 11/30/23

SUMMARY TEST DATA
ON
LM-10M14G-100W-1KWP-SFF-OPT17

