



**SUMMARY TEST DATA**  
**ON**  
**LM-10M14G-100W-1KWP-SFF-OPT17**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: LM-10M14G-100W-1KWP-SFF-OPT17  
 Serial No: PL43159/2349

Tested By: K Craven  
 Temperature: +25°C  
 Date: 12/4/2023  
 Drawing No: 27637020      REV: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	10 MHz to 7 GHz	10 MHz to 7 GHz	
2	Insertion Loss:	2 dB Typ.	0.96 dB See Graph	
3	Input/Output VSWR:	2.0:1 Max. @ -10 dBm Input	1.72:1 In 1.65:1 Out See Graph	
4	Impedance:	50 Ω	Pass	
5	Max. CW Input Power:	100W CW Max. (1.0 GHz to 7.0 GHz) All Temperatures (-55°C to +85°C)	Pass See Typical Characteristics	
6	Max. Pulsed Peak Power Handling:	1KW Peak (1% Duty Cycle, 1µs Pulse Width) 100W Peak (10% Duty Cycle, 10µs Pulse Width)	Pass See Typical Characteristics	
7	Max. Flat Leakage:	+17 dBm Typ. @ 100W CW	Pass See Typical Characteristics	
8	P1dB:	+ 5 dBm Min.	+ 6 dBm See Graph	
9	Recovery Time:	100 ns Max.	Pass See Typical Characteristics	

QA/QC Approval: *Cameron Kelley*

Date: 12/5/23

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731  
 Email: sales@pmi-rf.com

SUMMARY TEST DATA  
ON  
LM-10M14G-100W-1KWP-SFF-OPT17

