



SUMMARY TEST DATA
ON
LM-10M18G-16-20W-RAD-OPT418

Customer: _____
SO No: _____
Model No: LM-10M18G-16-20W-RAD-OPT418
Serial No: PL44013/2404

Tested By: John R.
Temperature: +25°C
Date: 2/8/2024
Drawing No: 27647380

REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	4 GHz to 18 GHz	4 GHz to 18 GHz	PMI QA4
2	Insertion Loss:	2.0 dB Max. @ -10 dBm Input Power	1.49 dB See Graph	
3	Leakage Power:	+15dBm Typ.	Pass See Typical Characteristics	
4	Impedance:	50 Ohms	Pass See Typical Characteristics	
5	Recovery Time (3 dB):	250 ns Max.	Pass See Typical Characteristics	
6	VSWR:	2.0:1 Max. @ -10 dBm Input Power	1.79:1 In 1.75:1 Out See Graph	
7	RF Power Handling:	20 W CW Max.	Pass See Typical Characteristics	
		500W Peak Max. (10 μ s PW, 1kHz PRF)	Pass See Typical Characteristics	
8	Limiting Threshold:	+ 5 dBm Nom. (1 dB Compression)	+ 9 dBm See Graph	PMI QA4

QA/QC Approval:

Camerez Kelly PMI
QA4


Date:

02/08/2024


SUMMARY TEST DATA ON LM-10M18G-16-20W-RAD-OPT418

PL44013/2404

Insertion Loss



VSWR



Limiter Response with Frequency

