



**SUMMARY TEST DATA
ON
P2T-1840-60-R-1W-292FF**

Customer: _____
 SO No: _____
 Model No: P2T-1840-60-R-1W-292FF
 Serial No: PL44081/2405

Tested By: S. O'Neill
 Temperature: 25°C
 Date: 1/31/2024
 Drawing No: 27647060 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	18 GHz to 40 GHz	18 GHz to 40 GHz	PMI QA2	
2	Insertion Loss (@ +25°C)	3.25 dB Typ. 3.5 dB Max.	3.44 dB		
3	Operating Power CW	1 Watts Max	Pass See Typical Characteristics		
4	VSWR: In/Out	2.5:1 Max. 2:1 Typ.	1.8:1 In 1.61:1 Out		
5	Isolation	60 dB Min.	61.9 dB		
6	Switching Speed	500 ns Max. 100 ns Typ.	Pass See Typical Characteristics		
7	Control Signal	TTL LOGIC '1' : J1-J2 Low Loss '0' : J1-J3 Low Loss	Pass		
8	Power Supply	12 V @ 100 mA Max. -15 V @ 50 mA Max.	12 V @ 20 mA -15 V @ 20 mA		PMI QA2

QA/QC Approval: PMI
QA2 Date: 1/31/2024

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@quanticpmi.com



