

SUMMARY TEST DATA ON PLDRO-19D050G-25M-EXT-ROHS

Customer: _____
SO No: _____
Model No: **PLDRO-19D050G-25M-EXT-ROHS**
Serial No: **PL44098/2405**

Tested By: **Rony Castellanos**
Temperature: **25°C**
Date: **1/31/2024**
Drawing No: **27647260** Rev: **A1**

TEST ITEM	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA/QC
1	Output Frequency	19.050 GHz	19.050 GHz	
2	Reference Frequency	25 MHz	25 MHz	
3	Input Power Level	+10 ±3 dBm	+10 ±3 dBm	
4	No Lock Break VSWR	3:1 Max	Pass	
5	Output Power Level	+13 to +15 dBm Min	14.6 dBm	
6	Output Spurious (10 MHz to 2 GHz)	-76 dBc Max	-78.8 dBc	
7	Output Harmonics	-20 dBc Min	-57.63 dBc	
8	Output SSB Phase Noise	-42 dBc/Hz @ 10 Hz Max -67 dBc/Hz @ 100 Hz Max -98 dBc/Hz @ 1 kHz Max -106 dBc/Hz @ 10 kHz Max -109 dBc/Hz @ 100 kHz Max -126 dBc/Hz @ ≥1 MHz Max	-56.39 dBc/Hz @ 10 Hz -90.32 dBc/Hz @ 100 Hz -112.05 dBc/Hz @ 1 kHz -115.52 dBc/Hz @ 10 kHz -117.36 dBc/Hz @ 100 kHz -137.46 dBc/Hz @ 1 MHz	
9	Reference Input Spurious	-80 dBc Max	-80 dBc Max	
10	External Reference Phase Noise	-110 dBc/Hz @ 10 Hz Max -137 dBc/Hz @ 100 Hz Max -156 dBc/Hz @ 1 kHz Max -165 dBc/Hz @ 10 kHz Max -168 dBc/Hz @ 100 kHz Max	-110 dBc/Hz @ 10 Hz Max -137 dBc/Hz @ 100 Hz Max -156 dBc/Hz @ 1 kHz Max -165 dBc/Hz @ 10 kHz Max -168 dBc/Hz @ 100 kHz Max	

*Spurious maximum measured value includes both wideband sweep spurs and sidebands close to carrier.

**SUMMARY TEST DATA
ON
PLDRO-19D050G-25M-EXT-ROHS**

PL44098/2405



TEST ITEM	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA/QC
11	Lock Detector	TTL High - In Lock; TTL Low - Out of Lock	TTL High - In Lock; TTL Low - Out of Lock	
12	Supply Voltage	+12±0.5V @ 500mA Max (@ 25°C)	+12 ± 0.5V @ 374 mA	
13	Phase Voltage Monitor Output	0V to +12V	0V to +12V	
14	Cold Start Temperature:	-45°C Max	-45°C Max	

QA/QC Approval: _____


Date: _____

**SUMMARY TEST DATA
ON
PLDRO-19D050G-25M-EXT-ROHS**

PL44098/2405



Phase Noise



15:40:59 18.12.2023

Harmonics

-57.63 dBc

