



**SUMMARY TEST DATA  
ON  
P6T-2G18G-55-R-512-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P6T-2G18G-55-R-512-SFF  
 Serial No: PL44384/2406

Tested By: L. McGraw  
 Temperature: 25°C  
 Date: 2/9/2024  
 Drawing No: 27613452 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	2 GHz to 18 GHz	2 GHz to 18 GHz	PMI QA4
2	Insertion Loss	7 dB Max.	5.79 dB	
3	Input Power	10 dBm CW Max Operating 25 dBm CW Max Survival	Pass See Typical Characteristics	
4	VSWR: In/Out	2:1 Max.	1.94:1 In 1.96:1 Out	
5	Isolation	55 dB Min.	60.9 dB	
6	Switching Speed Max	15 ns Max.	Pass See Typical Characteristics	
7	Video Transients	15 mv P-P Max.	Pass See Typical Characteristics	
8	Video Transients Spectral Content	60 dBm Max. 65 dBm Typ.	Pass See Typical Characteristics	
9	Power Supply	5 V @ 200 mA Max. -12 V @ 60 mA Max.	5 V @ 95 mA -12 V @ 5 mA	PMI QA4

QA/QC Approval: *Cameron Kelley* **PMI QA4** Date: 02/09/2024

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com



