



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**

PL44309/2406

Customer: _____ Tested By: Rony Castellanos
SO No: _____ Temperature: +25°C
Model No: PLDRO-12522R24M-13DBM-SFF Date: 02/07/2024
Serial No: PL44309/2406 Drawing No: 27034480 Rev: C1

TEST ITEM	PARAMETERS	SPECIFIED VALUE		TEST RESULTS	QA QC
1	Frequency Range (fo)	12.52224 GHz		12.52224 GHz	PMI QA4
2	External Reference	130.44 MHz		130.44 MHz	
3	Reference Input Power	0 ± 3 dBm		0 ± 3 dB	
4	Output Power	13 dBm Min		14.57 dBm	
5	Spurious	-70 dBc Max In Band		-83.4 dBc	
6	Harmonics	-20 dBc Max		-43.01 dBc	
7	Phase Noise	-67 dBc/Hz Min	100 Hz	Pass	
		-96 dBc/Hz Min	1 kHz		
		-110 dBc/Hz Min	10 kHz		
		-115 dBc/Hz Min	100 kHz		
		-130 dBc/Hz Min	1 MHz		
8	DC Power	+12 to +15V @ 350 mA Max		+15@ 220 mA	
9	Lock Detect	TTL High In Lock		Pass	PMI QA4

QA/QC Approval: *Carmenely Velazquez* ^{PMI}QA4 Date: 02/08/24




SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF

PL44309/2406


Carrier Signal

✱ Agilent 13:48:34 20 Jan 2024



Harmonics

✱ Agilent 17:00:48 20 Jan 2024



	Frequency	Amplitude
1	12.52 GHz	14.31 dBm
2	25.04 GHz	-35.00 dBc
3	37.57 GHz	-46.33 dBc
4	50.09 GHz	-43.01 dBc




SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF

PL44309/2406

Spurious

✱ Agilent 13:49:38 20 Jan 2024



Spur	Range	Frequency	Amplitude	Limit
17	2	1.909 GHz	-79.00 dBm	-50.00 dBm
18	2	1.903 GHz	-79.07 dBm	-50.00 dBm
19	2	1.898 GHz	-79.14 dBm	-50.00 dBm
20	2	1.918 GHz	-79.47 dBm	-50.00 dBm
21	5	969.1 MHz	-68.83 dBm	-50.00 dBm