



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF**

PL44702/2409

Customer: _____ Tested By: Rony Castellanos
SO No: _____ Temperature: +25°C
Model No: PLDRO-12522R24M-13DBM-SFF Date: 02/26/2024
Serial No: PL44702/2409 Drawing No: 27034480 Rev: C2

TEST ITEM	PARAMETERS	SPECIFIED VALUE		TEST RESULTS	QA QC
1	Frequency Range (fo)	12.52224 GHz		12.52224 GHz	Pass QA2
2	External Reference	130.44 MHz		130.44 MHz	
3	Reference Input Power	0 ± 3 dBm		0 ± 3 dB	
4	Output Power	13 dBm Min		15.42 dBm	
5	Spurious	-70 dBc Max In Band		-70 dBc	
6	Harmonics	-20 dBc Max		-30.07 dBc	
7	Phase Noise	-67 dBc/Hz Min	100 Hz	See Typ.	
		-96 dBc/Hz Min	1 kHz		
		-110 dBc/Hz Min	10 kHz		
		-115 dBc/Hz Min	100 kHz		
		-130 dBc/Hz Min	1 MHz		
8	DC Power	+12 to +15V @ 350 mA Max		+15 @ 210 mA	
9	Lock Detect	TTL High In Lock		Pass	Pass QA2


QA/QC Approval: P:ill QA2 Date: 2/28/2024




SUMMARY TEST DATA ON PLDRO-12522R24M-13DBM-SFF

PL44702/2409

Carrier Signal



Harmonics







SUMMARY TEST DATA ON PLDRO-12522R24M-13DBM-SFF

PL44702/2409

Spurious



Phase Noise Curve



Measurement Complete

Date: 14.APR.2024 21:00:37