

**SUMMARY TEST DATA  
ON  
P2T-0R3G18G-80-T-55-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P2T-0R3G18G-80-T-55-SFF  
 Serial No: PL45437/2415

Tested By: A. Mousavi  
 Temperature: +25° C  
 Date: 4/8/2024  
 Drawing No: 27629411 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	0.3 - 18.0 GHz	0.3 - 18.0 GHz	PMI QA2	
2	Insertion Loss:	3.5 dB Max.	3.02 dB See Plot		
3	Isolation:	80 dB Min.	80 dB See Plot		
4	VSWR:	In/Out: 2.0:1 Max. Terminated Out: 2.0:1 Max.	1.47:1 In/Out 1.39:1 Term. See Plot		
5	Rise Time:	50 nsec Max.	Pass See Typical Characteristics		
6	Fall Time:	50 nsec Max.	Pass See Typical Characteristics		
7	Input Power	20 dBm CW Max.	Pass See Typical Characteristics		
8	DC Supply:	+5 VDC @ 65 mA Max. -5 VDC @ 50 mA Max.	+5 VDC @ 40 mA -5 VDC @ 40 mA		PMI QA2

QA/QC Approval: \_\_\_\_\_



PMI  
QA2

Date: 4/8/2024

