



Tested By: Y Li/MS

Temperature: 25°C

Date: 4/30/2024

Drawing No: 27630800 Rev A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	LO Frequency Range	8 to 12 GHz	8 to 12 GHz	PMI QA2
2	LO Power	+14 dBm Min +15 dBm Typ +17 dBm Max	15 dBm	
3	LO VSWR	1.4:1 Typ	Pass By Design	
4	RF VSWR	3.1:1 Typ	Pass By Design	
5	Conversion Loss	7.5 dB Typ 10.5 dB Max	9.2 dB	
6	Noise Figure	8 dB Typ 9.5 dB Max	Pass By Design	
7	Input IP3	+23 dBm Typ	Pass By Design	
8	Input P1dB	+14dBm Typ	Pass By Design	
9	LO-RF isolation	40 dB Min 50 dB Typ	59.1 dB	
10	LO-IF isolation	55 dB Typ	Pass By Design	
11	Image Rejection	23 dB Min 33 dB Typ	56.1 dB	
12	LO/RF input Power W/O Damage	23 dBm Max	Pass By Design	PMI QA2

Date: 4/30/2024

Page 1 of 3

Conversion Loss




Image Rejection

