



## SUMMARY TEST DATA ON 6SFB-30M600M-CD-SFF

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: 6SFB-30M600M-CD-SFF  
 Serial No: PL46108/2420

Tested By: K. Wagaman  
 Temperature: 25°C  
 Date: 5/14/2024  
 Drawing No: 27636660      Rev: A1




TEST ITEM	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	30 MHz to 600 MHz	30 MHz to 600 MHz	PMI QA4
2	Insertion Loss	4.0 dB Typ., 4.5 dB Max.	Channel 1: 2 dB Channel 2: 1.9 dB Channel 3: 2 dB Channel 4: 1.8 dB Channel 5: 2.4 dB Channel 6: 2.5 dB	
3	Rejection Lower	dBc 1: 60 @ 15 MHz, 40 @ 20 MHz 2: 60 @ 20 MHz, 40 @ 25 MHz 3: 60 @ 20-35 MHz, 40 @ 40 MHz 4: 60 @ 20-55 MHz, 40 @ 55-65 MHz 5: 60 @ 20-100 MHz, 40 @ 100-115 MHz 6: 60 @ 20-180 MHz, 40 @ 180-190 MHz	Channel 1: 65.3, 45.1 Channel 2: 64.4, 53.3 Channel 3: 64.1, 57.2 Channel 4: 71, 63.2 Channel 5: 66.2, 52.5 Channel 6: 63.7, 71.3	
4	Rejection Upper	dBc 1: 40 @ 60-70 MHz, 60 @ 70-800 MHz 2: 40 @ 90-110 MHz, 60 @ 110-800 MHz 3: 40 @ 140-160 MHz, 60 @ 160-800 MHz 4: 40 @ 200-220 MHz, 60 @ 220-1000 MHz 5: 40 @ 320-340 MHz, 60 @ 340-1500 MHz 6: 40 @ 550-570 MHz, 60 @ 570-1500 MHz	Channel 1: 47.3, 68 Channel 2: 42.4, 69.7 Channel 3: 58.1, 68.7 Channel 4: 45.8, 66.7 Channel 5: 45, 69 Channel 6: 41.2, 65	
5	VSWR: In/Out	1.5:1 Max.	Channel 1: 1.4:1 Channel 2: 1.4:1 Channel 3: 1.3:1 Channel 4: 1.4:1 Channel 5: 1.4:1 Channel 6: 1.4:1	
6	Isolation	40 dB Min	68.9 dB	
7	Input Power	1 W Max	Pass See Typical Characteristics	
8	Switching Speed	500 ns Typ.	Pass See Typical Characteristics	
9	DC Supply	+15VDC @ 300 mA Max -15VDC @ 50 mA Max	+15VDC @ 285 mA -15VDC @ 29 mA	PMI QA4




\*Note: dBc Rejection Referenced to Passband Center Frequency




QA/QC Approval: *Cameron Kelley*

Date: 5/15/24




7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com
















7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: sales@pmi-rf.com










7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: sales@pmi-rf.com





7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: sales@pmi-rf.com

