



**SUMMARY TEST DATA
ON
P2T-218-60-R-1W-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-218-60-R-1W-SFF
 Serial No: PL46327/2422

Tested By: A. Mousavi
 Temperature: +25° C
 Date: 5/29/2024
 Drawing No: 27643760 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	0.2 - 18.0 GHz	0.2 - 18.0 GHz	PMI QA2	
2	Insertion Loss:	2.5 dB MAX.	1.71 dB See Plot		
3	Isolation:	60 dB MIN.	60 dB See Plot		
4	VSWR:	2.0:1 MAX	1.29 In/Out See Plot		
5	Switching Speed:	25 ns MAX	<50 ns See Typical Characteristics		
6	Operational Input Power:	Up to +23 dBm CW MIN	Pass		
8	DC Supply:	+5 VDC TO + 15 VDC @ 65 mA Max. -5 VDC TO -15 VDC @ 65 mA Max.	+5 TO +15 VDC @ 20 mA -5 TO -15 VDC @ 20 mA		
9	Control:	TTL "0" → (J1-J2) TTL "1" → (J1-J3)	Pass		PMI QA2

QA/QC Approval:  PMI
QA2

Date: 5/29/2024

