



SUMMARY TEST DATA  
ON  
P2T-500M18G-80-T-515-SFF-4W-ST

Customer: \_\_\_\_\_  
SO No: \_\_\_\_\_  
Model No: P2T-500M18G-80-T-515-SFF-4W-ST  
Serial No: PL46507/2423

Tested By: A. Mousavi  
Temperature: 25°C  
Date: 6/5/2024  
Drawing No: 27630243 Rev: B2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.5 GHz to 18 GHz	0.5 GHz to 18 GHz	PMI QA2
2	Isolation	70 dB Min.	70.9 dB	
3	Insertion Loss	3.5 dB Typ.	3.18 dB	
4	VSWR: In/Out	2.0:1 Max.	1.56:1 In 1.68:1 Out	
5	Operating Power CW	4 Watts Max	Pass See Typical Characteristics	
6	Operating Power Peak	20 Watts, 50ns PW, 2Mhz PRF, 10% Duty	Pass See Typical Characteristics	
7	Switching Speed	60 ns Max.	Pass See Typical Characteristics	
8	Power Supply	5 V @ 150 mA -15 V @ 150 mA	5 V @ 60 mA -15 V @ 80 mA	
9	Control Signal	TTL LOGIC '1' : J1-J2 Low Loss '0' : J1-J3 Low Loss	Pass	PMI QA2

QA/QC Approval:  \_\_\_\_\_  
PMI  
QA2

Date: 6/6/2024

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: sales@quanticpmi.com



