



**SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF-ROHS**

PL46816/2425

Customer: _____ Tested By: K Craven
SO No: _____ Temperature: +25°C
Model No: PLDRO-12522R24M-13DBM-SFF-ROHS Date: 6/19/24
Serial No: PL46816/2425 Drawing No: 27634480 Rev: B1

TEST ITEM	PARAMETERS	SPECIFIED VALUE		TEST RESULTS	QA QC
1	Frequency Range (fo)	12.52224 GHz		12.52224 GHz	PMI QA4
2	External Reference	130.44 MHz		130.44 MHz	
3	Reference Input Power	0 ± 3 dBm		0 ± 3 dB	
4	Output Power	13 dBm Min		14.30 dBm	
5	Spurious	-70 dBc Max In Band		-80.64 dBc	
6	Harmonics	-20 dBc Max		-33.96 dBc	
7	Phase Noise	-67 dBc/Hz Min	100 Hz	See Plot	
		-96 dBc/Hz Min	1 kHz		
		-110 dBc/Hz Min	10 kHz		
		-115 dBc/Hz Min	100 kHz		
		-130 dBc/Hz Min	1 MHz		
8	DC Power	+12 to +15V @ 350 mA Max		+15@ 210 mA	
9	Lock Detect	TTL High In Lock		Pass	PMI QA4

QA/QC Approval: _____

Cameron Velen

Date: _____

6/21/24




SUMMARY TEST DATA ON PLDRO-12522R24M-13DBM-SFF-ROHS

PL46816/2425


Carrier Signal

* Agilent



Harmonics

* Agilent



Frequency	Amplitude
1 12.52 GHz	14.62 dBm
2 25.04 GHz	-33.96 dBc
3 37.57 GHz	-37.56 dBc
4 50.09 GHz	-44.92 dBc




SUMMARY TEST DATA
ON
PLDRO-12522R24M-13DBM-SFF-ROHS

PL46816/2425


Spurious

Agilent



Spur	Range	Frequency	Amplitude	Limit
17	2	1.915 GHz	-78.37 dBm	-50.00 dBm
18	2	1.913 GHz	-78.47 dBm	-50.00 dBm
19	2	1.895 GHz	-78.53 dBm	-50.00 dBm
20	2	1.912 GHz	-78.64 dBm	-50.00 dBm
21	5	967.1 MHz	-66.64 dBm	-50.00 dBm

Phase Noise Curve



Measurement Complete