

SUMMARY TEST DATA

ON

11DP-11R5/16R5-CD-SFF

CUSTOMER:

SO:

MODEL NO: 11DP-11R5/16R5-CD-SFF

SERIAL NO: PL47533/2432

TESTED BY: K Craven

TEMPERATURE: +25

DATE: 8/8/2024

DRAWING NO: 27608608




Rev: A2

TEST ITEM	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	REMARKS QA/QC
1	Center Frequency	BPF1 - 11.5 GHz BPF2 - 16.5 GHz	BPF1 - 11.5 GHz BPF2 - 16.5 GHz	PMI QA2
2	Passband Frequency Range	BPF1 - 10.75 to 12.25 GHz BPF2 - 15.75 to 17.25 GHz	BPF1 - 10.75 to 12.25 GHz BPF2 - 15.75 to 17.25 GHz	
3	Insertion Loss @ Passband	2 dB Goal 3 dB Max	0.91 dB	
4	VSWR	1.5:1 Max.	1.35:1	
5	Rejection	BPF1 - -50 dBc Min @ 10.25 GHz -75 dBc Min @ 13.75 GHz BPF2 - -50 dBc Min @ 17.25 GHz -75 dBc Min @ 14.75 GHz	BPF1- -53.17 dBc -101.26 dBc BPF2- -51.95 dBc -106.98 dBc	
6	Return Loss Input/ Output	-14.0 dB Max.	-16.22 dB	PMI QA2




7th 7th

PMI
QA2

8/27/2024



**SUMMARY TEST DATA
ON
11DP-11R5/16R5-CD-SFF**



**SUMMARY TEST DATA
ON
11DP-11R5/16R5-CD-SFF**