



SUMMARY TEST DATA
ON
LM-30M2G-5CW-1KWP-SFF

Customer: _____
SO No: _____
Model No: LM-30M2G-5CW-1KWP-SFF
Serial No: PL48095/2437
Part No: _____

Tested By: John R.
Temperature: +25°C
Date: 9/10/2024
Drawing No: 27635700

REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	30 MHz to 2.0 GHz	30 MHz to 2.0 GHz	PMI QA4
2	Insertion Loss:	0.7 dB Goal, 1dB Max. @ 0 dBm Input	0.76 dB See Graph	
3	VSWR:	2.0: 1Max. @ 0 dBm Input	1.83:1 In 1.84:1 Out See Graph	
4	Impedance:	50 Ω	Pass	
5	Input Power:	5 W CW Min. 1 kW Peak (0.1% Duty Cycle, 1 μ s Max. Pulse Width)	Pass See Typical Characteristics	
6	Maximum Flat Leakage:	17 dBm (50 mW) Max.	Pass See Typical Characteristics	
7	Spike Leakage	1.0 x 10 ⁻⁸ kg m ² /sec ² Max. (0.1 ergs Max.)	Pass See Typical Characteristics	
8	Limiting Threshold:	7 dBm Min, 1 dB Compression	13 dBm See Graph	
9	Recovery Time (3 dB):	1 μ s Max @ 1KW Peak Power	Pass See Typical Characteristics	PMI QA4

1. EXTERNAL DC BLOCKS ARE REQUIRED FOR PROPER FUNCTION.

QA/QC Approval:

Date:


9/10/24

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com


SUMMARY TEST DATA ON LM-30M2G-5CW-1KWP-SFF

PL48095/2437

Insertion Loss @ 0dBm



VSWR @ 0 dBm



Limiter Response with Frequency

