



Summary Test Data
For
DD-816-P-SMF

Customer: _____
SO No: _____
Model No: DD-816-P-SMF
Serial No: PL49572/2441

Tested By: K Craven
Temperature: +25° C
Date: 10/9/2024
Drawing No: 27646740 REV: A2

Outline Specifications & Test Data

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Input Power	Test Results	QA/QC PMI QA2
				+25°	
1	Frequency Range	8 to 16 GHz		8 to 16 GHz	
2	VSWR In @ -23dBm	3.5:1 MAX. ¹	-10 dBm	3.27:1	
3	Frequency Flatness	±0.6 dB Typ, ±1.0 dB Max ^{1,2}	-10 dBm	±0.37dB	
4	TSS(5MHz Filter BW, 3dB NF amplifier)	-48 dBm MAX. ³	-48 dBm	-61 dBm See Plot	
5	Output Voltage vs Load	15 mV MIN @ 100 ohms/ 80 mV Min @ Open ¹	-10 dBm	33.7 mV @ 100 ohms 96 mV @ Open	PMI QA2
6	Video Polarity	Positive		Positive	

QA/QC APPROVAL




PMI
QA2




DATE 10/10/2024




¹Measured with 100Ω termination

²(mV in dB scale min to max)/2 (Measured -10dBm)


³Measured @ 12 GHz








-61dBm Input Pulse to Amplifier



*Output with 100 Ω termination
*1Mhz pulse frequency, 500 ns

Appendix A: TSS Calculations and Test Setup



Amplifier PMI Model PEC-36-2G18G-4R5-27-15-SFF Data

