Quantic PMI
PLANAR MONOLITHICS

SUMMARY TEST DATA
ON
P2T-218-60-512-R-SFF

Customer:		Tested By:	John Berrocal
SO No:		Temperature:	+25° C
Model No:	P2T-218-60-512-R-SFF	Date:	10/24/2024
Serial No:	PL49629/2442	Drawing No:	27643760 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2.0 GHz to 18.0 GHz	**2.0 GHz to 18.0 GHz**	PMI QA2
2	Insertion Loss:	1.8 dB Max.	**1.6 dB** **See Graph**	
3	Isolation:	60 dB Min.	**60.3 dB** **See Graph**	
4	VSWR:	1.9:1 Max.	**1.77:1 In** **1.71:1 Out** **See Graph**	
5	Switching Speed:	30 ns Max.	**Pass** See Typical Characteristics	
6	Operating Input Power:	1 Watt CW Max. 2W Pk, 1% DC, 100ns Max.	**Pass** See Typical Characteristics	
7	DC Supply:	+5 VDC @ 65 mA Max.. -12 VDC @ 65 mA Max.	**+5 VDC @ 16 mA** **-12 VDC @ 35 mA**	
8	Control:	Logic Table CTL1 / Function 1 / J1-J2 0 / J1-J3	**Pass**	PMI QA2

QA/QC Approval: [illegible] [illegible] PMI QA2 Date: 10/30/2024

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com

Quantic PMI
PLANAR MONOLITHICS

SUMMARY TEST DATA ON P2T-218-60-512-R-SFF

PL49629/2442







7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com