



**SUMMARY TEST DATA
ON
P1T-6G12G-80-T-SFF-1W**

Customer: _____
 SO No: _____
 Model No: P1T-6G12G-80-T-SFF-1W
 Serial No: PL49657/2442

Tested By: John Berrocal
 Temperature: 25°C
 Date: 11/5/2024
 Drawing No: 27628521 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	6 GHz to 12 GHz	6 GHz to 12 GHz	PMI QA4
2	Insertion Loss	1.75 dB Max.	1.74 dB	
3	Isolation	80 dB Min.	83.9 dB	
4	VSWR: In/Out	2.0:1 Max. (1.5:1 Goal)	1.29:1 In 1.3:1 Out	
5	Switching Speed	25 ns Typ.	Pass See Typical Characteristics	
6	Input Power	+30 dBm Max.	Pass See Typical Characteristics	
7	Control Signal	TTL LOGIC '0' : Insertion Loss '1' : Isolation	Pass	
8	DC Supply	+5VDC @ 50 mA Max. -15VDC @ 75 mA Max.	+ 5 VDC @ 45 mA - 15 VDC @ 65 mA	PMI QA4

QA/QC Approval: *Cameron Kelley*

Date: 11/6/24

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com



