

**SUMMARY TEST DATA
ON
P8T-20M18G-80-R-512-SFF**

Customer: _____

SO No: _____

Tested By: S. O'Neill

Temperature: +25° C

Model No: P8T-20M18G-80-R-512-SFF


Date: 10/24/2024

Serial No: PL49763/2443

Drawing No: 27616149

Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.012 GHz to 18 GHz	0.012 GHz to 18 GHz	PMI QA4
2	Isolation	80 dB Min.	82.1 dB	
3	Insertion Loss	4.5 dB Max. 4 dB Typ.	3.2 dB	
4	VSWR: In/Out	2:1 Max.	1.73:1 In 1.82:1 Out	
5	Input Power	23 dBm CW Max.	Pass See Typical Characteristics	
6	DC SUPPLY	+5VDC @ 300 mA Max. -12VDC @ 100 mA Max.	+5VDC @ 269 mA -12VDC @ 92 mA	
7	Switching Speed	1000 ns Max.	Pass See Typical Characteristics	PMI QA4



QA/QC Approval: _____

Camron Kelly

Date: 10/24/24

**SUMMARY TEST DATA
ON
P8T-20M18G-80-R-512-SFF**

