

**SUMMARY TEST DATA
ON
4SFB-2G6G-CD-5-N12-SFF**

Customer: _____
SO No: _____
Model No: 4SFB-2G6G-CD-5-N12-SFF
Serial No: PL50113/2446

Tested By: H. Gonzales
Temperature: +25°C
Date: 11/11/2024
Drawing No: 27610341 Rev: C1




TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2 GHz - 6 GHz	2 GHz - 6 GHz	PMI QA1
2	3 dB Bandwidth:	1 GHz Min.	Pass See Graphs	
3	Pass Band Ripple:	0.5 dB Peak to Peak	Pass 0.5 dB Peak to Peak See Graphs	
4	Insertion Loss:	5 dB Max.	4.19 dB See Graphs	
5	Impedance:	50 Ω	50 Ω	
6	Switching Speed:	2 μs Max.	<300 ns See Typical Characteristics	
7	Pass Band VSWR:	2.0:1 Max.	1.7:1 See Plots	
8	Control Line:	TTL Positive See Truth Table	Pass	
9	DC Supply:	+5 VDC @ 200 mA Max. -15 VDC @ 200 mA Max.	+5 VDC @ 44 mA -15 VDC @ 50 mA	
10	Stop Band Frequency and Attenuation:	15% of corner frequency 60 dB Min.	61 dB See Graphs	

TTL Truth Table		
CTL 1	CTL 2	Filter Path
0	1	2 - 3 GHz
0	0	3 - 4 GHz
1	0	4 - 5 GHz
1	1	5 - 6 GHz




QA/QC Approval: *Camron Kelly*

Date: 11/11/24




SUMMARY TEST DATA ON 4SFB-2G6G-CD-5-N12-SFF



**SUMMARY TEST DATA
ON
4SFB-2G6G-CD-5-N12-SFF**



**SUMMARY TEST DATA
ON
4SFB-2G6G-CD-5-N12-SFF**



**SUMMARY TEST DATA
ON
4SFB-2G6G-CD-5-N12-SFF**

