

**SUMMARY TEST DATA
ON
JTIDS-0001-SFM**

CUSTOMER: _____ TESTED BY: K Craven
SO: _____ TEMPERATURE: +25°C
MODEL NO: JTIDS-0001-SFM DATE: 1/13/2025
SERIAL NO: PL50937/2503 DRAWING NO: 27646040 REV: A1

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	Center Frequency	1085 MHz	1085 MHz	PMI QA4
2	Notched Bandwidth	250 MHz	250 MHz	
3	Passband Insertion Loss	6.0 dB MAX (DC - 910 MHz, 1260 - 2000 MHz)	4.78 dB (DC to 910 MHz)	
			5.51 dB (1260 to 2000 MHz)	
			See Graph	
4	Passband VSWR	2.0:1 TYP 3.5:1 MAX AT PASSBAND EDGES	2.73 :1 See Graph	
5	Rejection	-40 dBC MIN @ 960 to 1210 MHz	55.96 dBC See Graph	PMI QA4

QA/QC Approval:

Cameron Kelly

Date:

1/15/25

SUMMARY TEST DATA ON JTIDS-0001-SFM

