

SUMMARY TEST DATA ON P4T-100M50G-100-T-RD-292-OPT40

Customer: _____
SO No: _____
Model No: P4T-100M50G-100-T-RD-292-OPT40
Serial No: PL50947/2503

Tested By: S. O'Neill
Temperature: +25°C
Date: 1/14/2025
Drawing No: 27632641 REV: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA
			+25°C	QC
1	Frequency Range:	0.1 to 40 GHz	0.1 to 40 GHz	PMI QA4
2	Insertion Loss:	4.0 dB (0.1 to 18GHz) MAX	3.04 dB	
		7.0 dB (18 to 40GHz) MAX	6.38 dB	
			See Graphs	
3	VSWR Input/Output	2.0:1 (0.1 to 18GHz) MAX	1.74 :1	
		2.25:1 (18 to 40GHz) MAX	1.98 :1	
			See Graphs	
4	Isolation:	80 dB (0.1 to 1GHz) Min.	100.93 dB	
		90 dB (1 to 18GHz) Min.	98.26 dB	
		75 dB (18 to 40GHz) Min.	88.32 dB	
			See Graphs	
5	Switching Speed	50 ns Max.	Pass See Typical Characteristics	
6	Input Power:	+20 dBm CW Max.	Pass See Typical Characteristics	
7	Control Signal:	See TTL Logic Table	Pass	
8	DC Supply:	+5 VDC @ 200 mA Max. -5 VDC @ 200 mA Max.	+5 VDC @ 160 mA -5 VDC @ 131 mA	PMI QA4

QA/QC Approval:


Cummary Kelly

Date:


1/15/25

SUMMARY TEST DATA ON P4T-100M50G-100-T-RD-292-OPT40

Insertion Loss



Isolation



SUMMARY TEST DATA ON P4T-100M50G-100-T-RD-292-OPT40

