

SUMMARY TEST DATA ON IRMX-4G8G-55-35-SFF-LOW


Customer: PMI Tested By: Alex G.
Job No: 27650500 Temperature: +25°C
Model No: IRMX-4G8G-55-35-SFF-LOW Date: February 18th, 2025
Serial No: PL51216/2504 Drawing No: 27650500 Rev: A

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	4 to 8 GHz	Pass	PMI QA2
2	LO Power	+14 dBm Min +15 dBm Typ +17 dBm Max	Pass	PMI QA2
3	LO VSWR	1.4:1 Typ	Pass	
4	RF VSWR	2.0:1 Typ	Pass	
5	Conversion Loss	7.5 dB Typ 10 dB Max	Pass (See Plot)	
6	Noise Figure	8 dB Typ 10.5 dB Max	Pass	
7	Input IP3	+24 dBm Typ	Pass	
8	Input P1dB	+14 dBm Typ	Pass	
9	LO-RF Isolation	55 dB Typ 40 dB Min	Pass (See Plot)	
10	LO-IF Isolation	55 dB Typ	Pass (See Plot)	
11	Image Rejection	35 dB Typ 25 dB Min	Pass (See Plot)	
12	RF/IF Input Power W/O Damage	+23 dBm Max	Pass	PMI QA2


QA/QC Approval:  PMI QA2 Date: 2/20/2025

SUMMARY TEST DATA ON IRMX-4G8G-55-35-SFF-LOW

IMAGE REJECTION




CONVERSION LOSS



SUMMARY TEST DATA ON IRMX-4G8G-55-35-SFF-LOW

LO-RF ISOLATION



LO-IF Isolation

