Quantic PMI
PLANAR MONOLITHICS

SUMMARY TEST DATA ON HP2G-1780-CD-SS

Customer:
SO No:
Model No: HP2G-1780-CD-SS
Serial No: PL51408/2507

Tested By: K Craven
Temperature: +25°C
Date: 2/10/2025
Drawing No: 27612567 Rev: B3

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	PassBand:	2000 MHz to 18000 MHz	**2000 MHz to 18000 MHz**	PMI QA4
2	3 dB @ Cut Off:	1780 MHz	**1690 MHz**	
3	VSWR: (In PassBand	1.5:1 Typ. 2:1 Max..	**1.77:1 (See Plot)**	
4	Insertion Loss: (PassBand)	0.5 dB Typ. 1 dB Max..	**0.7 dB (See Plot)**	
5	Rejection: (at 870 MHz)	80 dB Min.	**90 dB (See Plot)**	PMI QA4

QA/QC Approval: Cameron Kelem

Date: 2/21/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com

PL51408/2507

SUMMARY TEST DATA
ON
HP2G-1780-CD-SS

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com