

**SUMMARY TEST DATA
ON
LM-20M15G-100W-15DBM**

Customer: _____
SO No: _____
Model No: LM-20M15G-100W-15DBM
Serial No: PL51724/2511

Tested By: A. Mousavi
Temperature: +25°C
Date: 3/11/2025
Drawing No: 27638620 REV: A2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	20 MHz to 15 GHz	20 MHz to 15 GHz	PMI QA4
2	Insertion Loss:	1.8 dB Max @ -10dBm Input Power	1.8 dB See Graph	
3	Input/Output VSWR:	2.0:1 Max. @ -10 dBm Input Power	1.96:1 In 1.94:1 Out See Graph	
4	RF Power Handling:	100W CW Max. @ -55C TO +85C 1kW Peak (1µs Max. PW, 0.1% Duty Cycle) 100W (1µs, 1% Duty Cycle, 10KHz) 100W (10µs, 0.1% Duty Cycle, 100Hz) 100W (1µs, 0.1% Duty Cycle, 1KHz) 100W (40µs, 10% Duty Cycle, 2.5KHz)	Pass See Typical Characteristics	
5	Leakage Power:	+15 dBm Max. Max. @100W CW	Pass See Typical Characteristics	
6	P1dB:	+5 dBm Min.	+ 5 dBm See Graph	
7	Recovery Time:	100 ns Typ.	Pass See Typical Characteristics	PMI QA4

QA/QC Approval:

Carmerenz Keleny

Date:

3/12/25

SUMMARY TEST DATA ON LM-20M15G-100W-15DBM

PL51724/2511

