

**SUMMARY TEST DATA
ON
JTIDS-0001-SFM-ROHS**

CUSTOMER: _____

TESTED BY: E. Kretz

SO: _____

TEMPERATURE: +25°C

MODEL NO: JTIDS-0001-SFM-ROHS

DATE: 3/12/2025

SERIAL NO: PL51726/2511

DRAWING NO: 27349900

REV: A1

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	Center Frequency	1085 MHz	1085 MHz	PMI QA2
2	Notched Bandwidth	250 MHz	250 MHz	
3	Passband Insertion Loss	6.0 dB MAX (DC - 910 MHz, 1260 - 2000 MHz)	2.9 dB (DC to 910 MHz)	
			5.58 dB (1260 to 2000 MHz)	
			See Graph	
4	Passband VSWR	2.0:1 TYP 3.5:1 MAX AT PASSBAND EDGES	3.44 :1 See Graph	
5	Rejection	-40 dBC MIN @ 960 to 1210 MHz	47.43 dBC See Graph	PMI QA2

QA/QC Approval: _____



PMI
QA2

Date: _____

3/18/2025

**SUMMARY TEST DATA
ON
JTIDS-0001-SFM-ROHS**

PL51726/2511

