



SUMMARY TEST DATA ON LM-118-100W-22DBM

Customer: _____
 SO No: _____
 Model No: LM-118-100W22DBM
 Serial No: PL51773/ 212

Tested By: K Craven
 Temperature: +25°C
 Date: 3/17/2025
 Drawing No: 27647900 Rev: B1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	1 to 18 GHz	1 to 18 GHz	PW/QA4
2	Insertion Loss:	3.0 dB Max. @ -10 dBm Input	2.59 dB See Graph	PW/QA4
3	Input/Output VSWR:	2.0:1 Max. @ -10 dBm Input	1.87:1 See Graph	
4	Leakage:	+22 dBm Max.	18.92 dBm See Graph	
5	Recovery Time:	100 ns Max. @100W Peak Power	Pass See Typical Characteristics	
6	RF Power Handling:	100 Watt CW Max. @-55°C to +85°C	Pass See Typical Characteristics	
		1KW Peak Max. (1µs PW, 0.1% Duty Cycle)	Pass See Typical Characteristics	
7	Limiting Threshold (P1dB):	+12 dBm Min.	+14 dBm See Graph	

QA/QC Approval: _____

Cammy Kelly

Date: 3/18/25

7309-A Grove Road Frederick, MD 21704 USA Phone: 301.662.5019 Fax: 301.662.1731
 Email: sales@QuanticPMI.com Web: www.QuanticPMI.com

SUMMARY TEST DATA ON LM-118-100W-22DBM

PL51773/2512



SUMMARY TEST DATA ON LM-118-100W-22DBM

PL51773/2512

