

**SUMMARY TEST
 ON
 LM-OR1G4G-100W-15DBM-SMF-ROHS**

Customer: _____
 SO No: _____
 Model: _____
 Serial No: PL52013/2513



Tested By: A. Lopez
 Temperature: +25°C
 Date: 3/28/2025
 Drawing No: 27649880 REV: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	0.1 to 4 GHz	0.1 to 4 GHz	PMI QA2
2	Insertion Loss: @ -10 dBm Input Power	1.5 dB Max.	0.84 dB See Graph	
3	VSWR: @ -10dBm Input Power	2.0:1 Max.	1.47 :1 See Graph	
4	RF Leakage Power: Flat	+15 dBm Max.	Pass See Typical Characteristics	
5	RF Input Power:	+50 dBm CW (100 W Max)	Pass See Typical Characteristics	
6	RF Input Peak Power:	+60 dBm CW 1 kW Max. 1% DC 1 us PW	Pass See Typical Characteristics	
7	Recovery Time:	'100 ns Max.	Pass See Typical Characteristics	



QA/QC Approval:  PMI
QA2

Date: 3/28/2025

SUMMARY TEST ON LM-0R1G4G-100W-15DBM-SMF-ROHS



SUMMARY TEST ON LM-0R1G4G-100W-15DBM-SMF-ROHS



7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com