



**SUMMARY TEST DATA  
ON  
LM-2G18G-RAD-3W-19DBM-SMF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: LM-2G18G-RAD-3W-19DBM-SMF  
 Serial No: PL52289/2515

Tested By: K. Wagaman  
 Temperature: +25°C  
 Date: 4/9/2025  
 Drawing No: 27646460      REV: A2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	2 GHz to 18 GHz	2 GHz to 18 GHz	QA QC  Pass Pass Pass
2	Insertion Loss:	2.5 dB Max.	1.7 dB See Graph	
3	VSWR:	2.0:1 Max.	1.84:1 In 1.83:1 Out See Graph	
4	Leakage Power:	80 mW (+19 dBm) Typ.	+ 15.43 dBm See Graph	
5	Power Handling:	3W CW Max. 1 kW Max. 0.1% DC 1 us PW	Pass See Typical Characteristics	
6	Recovery Time:	200 ns Max.	Pass See Typical Characteristics	

QA/QC Approval:

*Comarney Kelly*

Date:

4/10/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731  
 Email: sales@pmi-rf.com

**SUMMARY TEST DATA  
ON  
LM-2G18G-RAD-3W-19DBM-SMF**

