

**SUMMARY TEST DATA
ON
P2T-100M50G-100-T**

Customer: _____
 SO No: _____
 Model No: P2T-100M50G-100-T
 Serial No: PL52314/2515

Tested By: S. O'Neill
 Temperature: +25°C
 Date: 4/9/2025
 Drawing No: 26927766 REV: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
			+25°C	
1	Frequency Range:	0.1 to 50 GHz	Spec 0.1 to 50 GHz	FMI QA4
2	Insertion Loss:	4.5 dB (0.1 to 18 GHz) Max. 6.0 dB (18 to 40 GHz) Max. 8.5 dB (40 to 50 GHz) Max.	2.94 dB	
			4.57 dB	
			6.35 dB	
			See Graphs	
3	VSWR:	2.2:1 (0.1 to 18 GHz) Max. 2.5:1 (18 to 40 GHz) Max. 3.0:1 (40 to 50 GHz) Max.	1.64 :1	
			1.83 :1	
			1.89 :1	
			See Graphs	
4	Isolation:	85 dB (1 to 18 GHz) Min. 85 dB (18 to 40 GHz) Min. 70 dB (40 to 50 GHz) Min.	94.96 dB	
			86.34 dB	
			81.18 dB	
			See Graphs	
5	Input Power:	20 dBm CW Max.	Pass See Typical Characteristics	
6	Switching Speed:	50 ns Max.	Pass See Typical Characteristics	
7	Control Signal:	TTL Logic "0" = J1-J2 On TTL Logic "1" = J1-J3 On	Pass	
8	DC Voltage:	+5 VDC @ 100 mA Max. -5 VDC @ 100 mA Max.	+5 VDC @ 88 mA -5 VDC @ 64 mA	

QA/QC Approval: *Carmona Kelly*

Date: 4/10/25



