



**SUMMARY TEST DATA  
ON**

**P1T-DC40G-65-T-292FF-1NS-OPT18G**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G  
 Serial No: PL52756/2518

Tested By: Darwin M.C.  
 Temperature: 25°C  
 Date: 4/29/2025  
 Drawing No: 27625063 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	DC to 18 GHz	DC to 18 GHz	PMI QA4
2	Isolation	55 dB Min. 60 dB Typ.	59.1 dB	
3	Insertion Loss	5 dB Max. 4.5 dB Typ.	3.89 dB	
4	VSWR: In/Out	2.2:1 Max. 2:1 Typ.	1.71:1 In 1.74:1 Out	
5	Operating Power CW	17 dBm Max	Pass See Typical Characteristics	
6	Switching Speed	7 ns Max. 6 ns Typ.	Pass See Typical Characteristics	
7	Rise/Fall Time	2 ns Max. Rise 1 ns Typ. Rise 2 ns Max. Fall 1 ns Typ. Fall	Pass See Typical Characteristics	
8	Control Signal	TTL LOGIC '1' : Insertion Loss '0' : Isolation	Pass	
9	Video Transients	85mV P-P @ 300Mhz BW 2-18 GHz 15mV P-P @ 20Mhz BW 2-18 GHz	Pass See Typical Characteristics	
10	Power Supply	8 to 15 V @ 15 mA -8 to -15 V @ 40 mA	15 V @ 5 mA -15 V @ 27 mA	

QA/QC Approval: *Cumersony Kelong*

Date: 5/1/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com



