


**SUMMARY TEST DATA
ON
P2T-0R3G18G-80-T-55-SFF**

Customer: _____
 SO No: _____
 Model No: P2T-0R3G18G-80-T-55-SFF
 Serial No: PL52986/2520

Tested By: Darwin M.C.
 Temperature: 25°C
 Date: 5/13/2025
 Drawing No: 27631721 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.3 GHz to 18 GHz	0.3 GHz to 18 GHz	
2	Insertion Loss	3.5 dB Max.	2.9 dB	
3	Isolation	80 dB Min.	84.1 dB	
4	VSWR: In/Out	2:1 Max.	1.84:1 In 1.91:1 Out	
5	VSWR: Output/Off	2:1 Max.	1.81:1	
6	Rise Time Fall Time	50 ns Max. 50 ns Max.	Pass See Typical Characteristics	
7	Input Power	20 dBm CW Max.	Pass See Typical Characteristics	
8	DC Supply	+5VDC @ 65 mA Max. -5VDC @ 50 mA Max.	+ VDC @ 23 mA - VDC @ 40 mA	

QA/QC Approval: *Cameron Kelly*

Date: 5/14/25

