



SUMMARY TEST DATA ON LM-10M2D5G-100CW-1KWP-SFF-ROHS

Customer: _____
 SO No: _____
 Model No: LM-10M2D5G-100CW-1KWP-SFF-ROHS
 Serial No: PL53023/2520

Tested By: John R.
 Temperature: +25°C
 Date: 5/14/2025
 Drawing No: 27647880 REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	10 MHz to 2.5 GHz	10 MHz to 2.5 GHz	PMI QAA _____ _____ _____ _____ _____ _____ _____ PMI QAA
2	Insertion Loss:	0.8 dB Max.	0.57 dB See Graph	
3	VSWR:	1.3:1 Max. @ -10 dBm Input (Notes 1,2)	1.18:1 In 1.14:1 Out See Graph	
4	Impedance:	50 Ω	Pass	
5	Input Power:	100W CW Maximum 1KW Peak (1% DUTY CYCLE, 1μS Maximum Pulse Width) (Notes 1,2,3,4)	Pass See Typical Characteristics	
6	Flat Leakage:	+14 dBm Max. @ 10W CW	Pass See Typical Characteristics	
7	P1dB:	0 dBm Min.	+ 7 dBm See Graph	
8	Recovery Time:	2 μS Typ.	Pass See Typical Characteristics	

Notes:

1. POWER RATING AT 25°C: DERATED LINEARLY TO ZERO AT 150°C
2. HIGH POWER TEST DURATION: FULL RATED POWER FOR 10 SECONDS
3. HIGH POWER PEAK CONDITIONS: 1KW PEAK (1% DUTY CYCLE, 1USEC MAXIMUM PULSE WIDTH)
4. EXTERNAL DC BLOCKS ARE REQUIRED FOR PROPER FUNCTION.

QA/QC Approval: *Commercy Klem*

Date: 5/15/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
 Email: sales@pmi-rf.com

