

**SUMMARY TEST DATA
ON
P2T-8G18G-50-R-SFFF**

Customer: _____
SO No: _____
Model No: P2T-8G18G-50-R-SFFF
Serial No: PL53367/2524

Tested By: K Craven
Temperature: +25°C
Date: 6/9/2025
Drawing No: 27634020 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	8.0 GHz to 18.0 GHz	8.0 GHz to 18.0 GHz	PMI QA4
2	Insertion Loss:	3.0 dB MAX	2.98 dB See Plot	
3	Isolation:	50dB Min	50 dB Typ. See Plot	
4	VSWR:	2.0:1 MAX	In 1.77:1 See Plot	
5	Switching Speed:	200 ns MAX	ON: <50 ns OFF: <200 ns See Typical Characteristics	
6	Operational Input Power:	40 W Max.	40 Watts (CW) See Typical Characteristics	
7	Peak Power:	300 W Max.	300 Watts See Typical Characteristics	
8	Pulse Width:	10 µs Max.	10 µs See Typical Characteristics	
9	Duty Cycle:	13% Max.	13% See Typical Characteristics	
10	DC Supply:	+5 VDC @ 150 mA MAX -28 VDC @ 80 mA MAX	+5 VDC @ 100 mA -28 VDC @ 3 mA	
11	Control:	TTL "0" → (J1-J2) TTL "1" → (J1-J3)	TTL "0" → (J1-J2) TTL "1" → (J1-J3)	

QA/QC Approval: *Cameron Kelly*

Date: 6/18/25

