

**SUMMARY TEST DATA
ON
P8T-0D418-75-T-SFF-NG**

Customer: _____
 SO No: _____
 Model No: P8T-0D418-75-T-SFF-NG
 Serial No: PL54009/2528

Tested By: L. McGraw
 Temperature: 25°C
 Date: 7/9/2025
 Drawing No: 27650320 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.4 GHz to 18 GHz	0.4 GHz to 18 GHz	PMI QA2
2	Isolation	75 dB Min.	76.6 dB	
3	Insertion Loss	3.4 dB Max., 0.4-10 GHz 4.5 dB Max., 10-18 GHz	3.13 dB 4.47 dB	
4	Return Loss (All Ports On Or Off)	-10 dB Min.	-11.86 dB J0 -10.62 dB J1-J8 -10.52 dB J1-J8 Off	
5	Power Supply	5 V @ 250 mA Max. -12 V @ 100 mA Max.	5 V @ 168 mA -12 V @ 75 mA	PMI QA2

QA/QC Approval:  **PMI QA2** Date: 7/10/2025

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@quanticpmi.com



