

**SUMMARY TEST
ON
PA-218-45-5-2W-24V-SFF**

Customer: _____
SO No: _____
Model No: PA-218-45-5-2W-24V-SFF
Serial No: PL54442/2530

Tested By: A. Mousavi
Temperature: +25° C
Date: 5/9/2026
Drawing No: 27645180 REV: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
			+25°C	
1	Frequency Range:	2.0 - 18.0 GHz	2.0 - 18.0 GHz	PMI QA5
2	Gain:	42 dB Min. 56 dB Max.	52.38 dB Max. 50.16 dB Min. See Graph	PMI QA5
3	Gain Flatness:	±3.5 dB Max.	1.11 dB See Graph	
4	VSWR: (Input)	2.0:1 Max.	1.81 :1 See Graph	
5	VSWR: (Output)	2.4:1 Max.	2.05 :1 See Graph	
6	Noise Figure:	5.0 dB Max	3.16 dB See Graph	
7	PSAT:	2W Min. (33 dBm) @ 0 dBm Input Power Min	+38.71 dBm Max.	
			+35.82 dBm Min.	
			See Graph	
8	Maximum Input Power:	+20 dBm Max.	Pass	
9	DC Voltage Supply:	+24 VDC @ 800 mA Max. (No RF) @ 1.6 A Max. P _{sat}	+24 VDC @ 620 mA.(No RF) @ 1.4 A.(P _{sat})	PMI QA5



QA/QC Approval:

Jordan Syed

Date:



5-12-26

SUMMARY TEST ON PA-218-45-5-2W-24V-SFF






SUMMARY TEST

PA-218-45-5-2W-24V-SFF



SUMMARY TEST ON PA-218-45-5-2W-24V-SFF



7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@pmi-rf.com