



SUMMARY TEST DATA ON P8T-0R5G18G-60-T-SFF-BR

Customer: _____
 SO No: _____
 Model No: P8T-0R5G18G-60-T-SFF-BR
 Serial No: PL54558/2531

Tested By: L. McGraw
 Temperature: +25°C
 Date: 7/29/2025
 Drawing No: 27633020 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	0.5 - 18 GHz	0.5 - 18 GHz	
2	Isolation:	60 dB Min.	82 dB See Graph	
3	Insertion Loss:	4.5 dB Typ. 5.0 dB Max.	4.9 dB See Graph	
4	VSWR: (In/Out)	2.0:1 Max.	1.91:1 In 1.89:1 Out See Graph	
5	Operating Input Power:	+30 dBm (1 Watt) Max.	See Typical Characteristics	
6	Switching Speed:	100 ns Typ.	See Typical Characteristics	
7	DC Supply:	+5 VDC @ 400 mA Typ. -5 VDC @ 200 mA Typ.	+5 VDC @ 235 mA -5 VDC @ 145 mA	
8	Control Signal:	Eight Line TTL E1 Controls J1-J2 E1 Controls J1-J2 "0" Isolation "1" Insertion Loss	Pass	



QA/QC Approval: 

Date: 7/30/25



SUMMARY TEST DATA ON P8T-0R5G18G-60-T-SFF-BR

PL54558/2531





SUMMARY TEST DATA ON P8T-0R5G18G-60-T-SFF-BR

PL54558/2531

