

**SUMMARY TEST  
ON  
PA-618-25G-6NF-30DBM-15V-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: PA-618-25G-6NF-30DBM-15V-SFF  
 Serial No: PL54795/2532

Tested By: A. Lopez  
 Temperature: +25°C  
 Date: 8/11/2025  
 Drawing No: 27650820      REV: A2




TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC	
1	Frequency Range:	6.0 - 18.0 GHz	6.0 - 18.0 GHz	PMI QA2	
2	Gain:	25 dB Typ. 20 dB Min. 28 dB Max.	+ 23.91 dB Max. + 23.15 dB Min. See Graph		
3	Gain Flatness:	±2.6 dB Max.	±0.38 dB See Graph		
4	VSWR: (In/Out)	2.0:1 Max.	1.74 :1 See Graph		
5	Input Power	27 dBm Max.	Pass See Typical Characteristics		
6	OP1dB:	30 dBm Typ.	+ 30.64 dBm See Graph		
7	Noise Figure:	5 dB Typ. 8.5 dB Max	4.25 dB See Graph		
8	DC Supply:	+15 VDC @ 1 A (Iq)	+15 VDC @ 820 mA		
9	Detection of Overheat (Temp)	"0" = OVERHEAT WITH AUTOMATIC SHUTOFF "3.3V" = NORMAL OPERATION	Set "0V" = Automatic ShutOFF "3.3V" = Operation		PMI QA2

QA/QC Approval: 

PMI  
QA2

Date: 8/19/2025

## SUMMARY TEST ON PA-618-25G-6NF-30DBM-15V-SFF



**SUMMARY TEST  
ON  
PA-618-25G-6NF-30DBM-15V-SFF**

