



SUMMARY TEST DATA ON P12T-0R5G18G-60-T-SFF

Customer: _____
 SO No: _____
 Model No: P12T-0R5G18G-60-T-SFF
 Serial No: PL54983/2534

Tested By: S. O'Neill
 Temperature: +25° C
 Date: 8/25/2025
 Drawing No: 27631860 Rev: B1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA
			+25°C	QC
1	Frequency Range:	0.5 to 18 GHz	0.5 to 18 GHz	PMI QA4 PMI QA4
2	Isolation:	60 dB Minimum	84.82 dB See Graphs	
3	Insertion Loss:	5.5 dB Maximum	4.52 dB See Graphs	
4	VSWR (In/Out):	2.0:1 Max.	1.84:1 See Graphs	
5	Switching Speed:	100 ns Max.	Pass See Typical Characteristics	
6	Power Handling:	+25 dBm CW Max.	Pass See Typical Characteristics	
7	Control:	TTL, 4 Bit (See Logic Table)	TTL, 4 Bit (See Logic Table)	
8	DC Supply:	+5V @ 600 mA Max. -5V @ 200 mA Max.	+5V @ 310 mA -5V @ 73 mA	

LOGIC TABLE				
E4	E3	E2	E1	CONNECTOR
0	0	0	0	J2 ON
0	0	0	1	J3 ON
0	0	1	0	J4 ON
0	0	1	1	J5 ON
0	1	0	0	J6 ON
0	1	0	1	J7 ON
0	1	1	0	J8 ON
0	1	1	1	J9 ON
1	0	0	0	J10 ON
1	0	0	1	J11 ON
1	0	1	0	J12 ON
1	0	1	1	J13 ON



QA/QC Approval: *Cameron Kelly*

Date: 8/25/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@pmi-rf.com



SUMMARY TEST DATA ON P12T-0R5G18G-60-T-SFF





SUMMARY TEST DATA ON P12T-0R5G18G-60-T-SFF

