



**SUMMARY TEST DATA
ON
P2T-500M40G-60-T-55-292FF**

Customer: _____
 SO No: _____
 Model No: P2T-500M40G-60-T-55-292FF
 Serial No: PL55130/2535




Tested By: W. Gonzalez
 Temperature: 25°C
 Date: 8/26/2025
 Drawing No: 27616616 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.5 GHz to 40 GHz	0.5 GHz to 40 GHz	PMI QA4
2	Isolation	55 dB Min.	59.7 dB	
3	Insertion Loss	6 dB Max.	5.65 dB	
4	VSWR: In/Out	2.5:1 Typ.	2.35:1 In 2.36:1 Out	
5	Operating Power CW	20 dBm Max	Pass See Typical Characteristics	
6	Survival Power Peak	1 W Max 1 uS Pulse Width	Pass See Typical Characteristics	
7	Rise/Fall Time	15 ns Max. Rise 15 ns Max. Fall	Pass See Typical Characteristics	
8	Delay On/Off	50 ns Max. On 50 ns Max. Off	Pass See Typical Characteristics	
9	Power Supply	5 V @ 200 mA Max. -5 V @ 100 mA Max.	5 V @ 50 mA -5 V @ 50 mA	
10	Control Signal	TTL LOGIC '0' : J1-J2 Low Loss '1' : J1-J3 Low Loss	Pass	

QA/QC Approval: *Cameron Kelly*

Date: 8/27/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@quanticpmi.com



7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@quanticpmi.com

