



**SUMMARY TEST DATA
ON
LM-26G40G-14-20W-292MM**

Customer: _____
 SO No: _____
 Model No: LM-26G40G-14-20W-292MM
 Serial No: PL55157/2536

Tested By: John R.
 Temperature: +25°C
 Date: 9/2/2025
 Drawing No: 27645320

REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	26.5 GHz to 40 GHz	26.5 GHz to 40 GHz	PMI QA4
2	Insertion Loss:	4 dB Max.	2.02 dB See Graph	
3	VSWR:	2.0:1	1.72:1 In 1.77:1 Out See Graph	
4	Leakage Power:	+14 dBm Typ.	+ 13.89 dBm See Graph	
5	Peak Input Power:	20W @ 440-670 ns Pulse Width PRF 600 to 900 kHz 40% Duty Cycle	Pass See Typical Characteristics	
6	Recovery Time to 1dB:	250 ns Max.	Pass See Typical Characteristics	

QA/QC Approval: *Cummins*

Date: 9/2/25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
 Email: sales@pmi-rf.com

**SUMMARY TEST DATA
ON
LM-26G40G-14-20W-292MM**

