



**SUMMARY TEST DATA  
ON  
P2T-10M8G-45-R-50W-AL**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P2T-10M8G-45-R-50W-AL  
 Serial No: PL56700/2547

Tested By: L.McGraw  
 Temperature: 25°C  
 Date: 11/21/2025  
 Drawing No: 27639180 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	0.01 GHz to 8 GHz	0.01 GHz to 8 GHz	PMI QAS	
2	Operating Power CW	50 Watts Average Cold Switching	Pass See Typical Characteristics	PMI QAS	
3	Insertion Loss	1 dB Max., 0.01-0.5 GHz 1.2 dB Max., 0.5-1 GHz 1.4 dB Max., 1-2 GHz 1.8 dB Max., 2-4 GHz 2.3 dB Max., 4-6 GHz 3 dB Max., 6-8 GHz	0.89 dB 0.77 dB 0.92 dB 1.4 dB 2.05 dB 2.94 dB		
4	Isolation	53 dB Min., 0.01-0.5 GHz 48 dB Min., 0.5-1 GHz 42 dB Min., 1-2 GHz 38 dB Min., 2-4 GHz 36 dB Min., 4-6 GHz 36 dB Min., 6-8 GHz	59.3 dB 55.9 dB 49.3 dB 43.5 dB 41 dB 38.2 dB		
5	VSWR: In/Out	2:1 Max., 0.01-0.5 GHz 1.5:1 Max., 0.5-1 GHz 1.5:1 Max., 1-2 GHz 1.5:1 Max., 2-4 GHz 1.8:1 Max., 4-6 GHz 1.9:1 Max., 6-8 GHz	1.95:1 1.31:1 1.31:1 1.49:1 1.74:1 1.88:1		
6	Switching Speed	100 ns Max.	Pass See Typical Characteristics		
7	Hot Switching	50 W (CW) MAX (1KHz, *, @ 20MHz) 40 W (CW) MAX (1KHz, *, @ 100MHz to 8 GHz) 20 W (CW) MAX (1MHz, *, @ 20MHz) 16 W (CW) MAX (1MHz, *, @ 100MHz to 0.5 GHz) 10 W (CW) MAX (1MHz, *, @ 8MHz)	Pass See Typical Characteristics		
8	Power Supply	5 V @ 100 mA Max.	5 V @ 40 mA		PMI QAS

\*50% Duty Cycle

QA/QC Approval: Jordan Syed Date: 11-21-25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com



