



**SUMMARY TEST DATA
ON
P2T-10M8G-45-R-50W-AL**

Customer: _____
 SO No: _____
 Model No: P2T-10M8G-45-R-50W-AL
 Serial No: PL56701/2547

Tested By: L.McGraw
 Temperature: 25°C
 Date: 11/21/2025
 Drawing No: 27639180 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.01 GHz to 8 GHz	0.01 GHz to 8 GHz	PMI QA5
2	Operating Power CW	50 Watts Average Cold Switching	Pass See Typical Characteristics	
3	Insertion Loss	1 dB Max., 0.01-0.5 GHz 1.2 dB Max., 0.5-1 GHz 1.4 dB Max., 1-2 GHz 1.8 dB Max., 2-4 GHz 2.3 dB Max., 4-6 GHz 3 dB Max., 6-8 GHz	0.84 dB 0.79 dB 0.97 dB 1.42 dB 1.87 dB 2.69 dB	
4	Isolation	53 dB Min., 0.01-0.5 GHz 48 dB Min., 0.5-1 GHz 42 dB Min., 1-2 GHz 38 dB Min., 2-4 GHz 36 dB Min., 4-6 GHz 36 dB Min., 6-8 GHz	59 dB 55.4 dB 50 dB 43.7 dB 41.4 dB 37.9 dB	
5	VSWR: In/Out	2:1 Max., 0.01-0.5 GHz 1.5:1 Max., 0.5-1 GHz 1.5:1 Max., 1-2 GHz 1.5:1 Max., 2-4 GHz 1.8:1 Max., 4-6 GHz 1.9:1 Max., 6-8 GHz	1.85:1 1.33:1 1.37:1 1.49:1 1.71:1 1.66:1	
6	Switching Speed	100 ns Max.	Pass See Typical Characteristics	
7	Hot Switching	50 W (CW) MAX (1KHz, * ,@ 20MHz) 40 W (CW) MAX (1KHz, * ,@ 100MHz to 8 GHz) 20 W (CW) MAX (1MHz, * ,@ 20MHz) 16 W (CW) MAX (1MHz, * ,@ 100MHz to 0.5 GHz) 10 W (CW) MAX (1MHz, * ,@ 8MHz)	Pass See Typical Characteristics	
8	Power Supply	5 V @ 100 mA Max.	5 V @ 40 mA	PMI QA5

*50% Duty Cycle

QA/QC Approval: Jordan [Signature]

Date: 11-21-25

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
 Email: sales@quanticpmi.com



